

BorderNet[™] Session Border Controllers supercharge connections between networks, services and subscribers with ease and scale

The Dialogic® BorderNet™ Virtualized Session Border Controller (SBC) brings carrier class SBC functionality to the cloud and enables service providers and enterprises to take advantage of flexibility and cost savings opportunities from virtualization. The BorderNet Virtualized SBC can interconnect IP networks securely and seamlessly, with unmatched ease of use and low total cost of ownership (TCO) to help secure mission critical infrastructure and reduce the cost of delivering services.

The BorderNet Virtualized SBC is designed to operate in virtualized public and private cloud environments to address complex service delivery challenges involving security, network interoperability, media handling, and reliability encountered in today's demanding service provider and enterprise networks.

Features	Benefits
Carrier Class in the Cloud SBC features	 High performance full featured software SBC with VMware hypervisor support
	Virtualized High Availability (HA) mode
	 SBC security includes DoS protection, encryption, overload protection, and threat mitigation to protect "mission critical" infrastructure and services
Rapid deployment and low TCO	 Modern Web 2.0 UI with real time dashboard, alarming and analytics for fast and intuitive configuration and system management
	 Operational consistency with the BorderNet[™] 4000 SBC and interoperable with the Dialogic[®] ControlSwitch[™] System to help reduce OPEX
	Flexible licensing options for cost effective scalability
	 Open Virtualization Format (OVF) compliant for fast deployment and implementation

BorderNet[™] Session Border Controllers supercharge connections between networks, services and subscribers with ease and scale



Examples of Applications

The BorderNet Virtualized SBC leverages virtualized computing environments to help make networks easier to connect. Example applications for the BorderNet Virtualized SBC include:

- Interconnecting IP Multimedia Subsystem (IMS), Voice over LTE (VoLTE), and IPX networks
- Interconnecting diverse SIP and H.323 mobile and fixed networks
- Detecting and reducing fraud
- IPv4 to IPv6 migration initiatives
- Managing multiple peering partners
- Traffic cost optimization and improved service quality
- Data center provider Infrastructure as a Service (IaaS) opportunities

Carrier Class in the Cloud Features

Feature Rich, High Performance Software SBC Solution

The BorderNet Virtualized SBC brings carrier class functionality to virtualized environments and can be deployed in a standalone or redundant (High Availability) configuration. Each instance of the BorderNet Virtualized SBC can support up to 8,000 simultaneous sessions at a rate of 30 sessions per second.

Advanced Security Features

SBCs provide a first line of defense against fraud and malicious attacks in service provider networks. The BorderNet Virtualized SBC helps protect network integrity and service quality from being compromised by providing a set of layered security capabilities that include the following:

- Customizable signaling and media topology hiding
- Built-in firewall capabilities
- Dynamic access control lists
- Automated rate limiting to protect against DoS attacks and DDoS
- · Real-time inspection of message syntax and semantics
- Protection against malformed messages
- Encryption, including TLS, IPsec, SRTP pass-through and HTTPS
- Message flood protection
- Dynamic Black Listing
- Media-related security, including pin-hole management, rogue RTP detection and bandwidth control
- Adaptive overload controls for the delivery of high priority and emergency traffic

Real-time Dashboard, User Management and Reporting Capabilities

The BorderNet Virtualized SBC features WebUI technology that is also available with the BorderNet 4000 SBC. This WebUI provides a real-time view into the activities on the BorderNet Virtualized SBC in the form of an operator dashboard to monitor key aspects of the SBC. The configuration and provisioning tasks related to the Virtualized SBC are performed through the highly intuitive WebUI.

In addition to typical OAM&P functions, the WebUI also provides feature-rich analytics and reporting. The analytics available from the WebUI include traffic statistics, usage summary, and a comprehensive set of performance and traffic reports to help manage network and service activity. The BorderNet Virtualized SBC's WebUI includes a role-based user administration function to secure and control access to various system views involving configuration and provisioning of the SBC. Additional tools are included in the WebUI to make license management, data archiving, historical reporting, regulatory compliance and network troubleshooting easy and streamlined.

BorderNet[™] Session Border Controllers supercharge connections between networks, services and subscribers with ease and scale



Powerful and Easy-to-Use Management, Interworking and Configuration Tools for Low TCO

Service providers need to securely connect their networks with other operators to deliver business and consumer services to their customers; however, not all SIP implementations are the same. Dialogic has developed the SIP Profiler for the BorderNet SBCs - including the Virtualized SBC - to help reduce the complexity of this process. The SIP Profiler is a powerful configuration tool that can help reduce the time and effort to implement interconnection in multi-vendor, multi-application environments across networks and enterprise end points with different SIP behaviors.

The SIP Profiler can be used to define behavior at the ingress and egress ports of the BorderNet Virtualized SBC and enable customized routing to help optimize and control SIP message flows. The SIP Profiler is accessed through the Virtualized SBC's WebUI, or through the use of XML scripts. Types of operations that can be performed using the SIP Profiler include:

- · Add, modify or delete SIP headers, SIP bodies and SDP parameters and adaptively impact message sequence and flows
- Store information from header fields for later access
- Inspect SIP messages for specific content
- Use customized response codes when, for example, rejecting messages

A Media Profiler extends the core features of the powerful SIP Profiler framework to the SDP, media attributes, and the codecs used in the bearer plane. The Media Profiler provides the ability to:

- Control and reorder the offered codec list
- Control media attributes
- Manage and manipulate contents of ISUP, QSIG and other non-SDP message bodies

The BorderNet Virtualized SBC's WebUI can simplify operational tasks associated with configuring and maintaining the integrity of a peering and access environment. The profile-based provisioning capabilities through the BorderNet Virtualized SBC WebUI allow users to define common sets of service, security, VoIP parameter, and media attributes that describe the behavior of a connected endpoint through the use of templates. The template-based provisioning approach can significantly reduce the time needed to turn up service and also the system knowledge required to do so. These powerful configuration features can also help lessen TCO and accelerate service delivery by reducing the complexity traditionally involved in establishing interworking and access connectivity.

The BorderNet Virtualized SBC includes both IP level and session level tracing, media capture and recording. It also includes SOAP/XML and bulk loading of interface configurations along with a northbound API for integration with existing BSS/OSS applications. System software upgrades can be easily accomplished through the WebUI, with the ability to roll back to an earlier software release version if needed.

BorderNet[™] Session Border Controllers supercharge connections between networks, services and subscribers with ease and scale

Datasheet

Technical Specifications

Protocol Interworking

Signaling SIP, SIP-I, SIP-T, H.323

Other VLAN, IPv4, IPv6, UDP, TCP, RTP, RTCP
Network IPv4, IPv6, overlapped IP networks

Security Features

Access Control List

Signaled pinhole media firewall

Network topology hiding for both signaling and media

Encryption support: TLS, IPsec, HTTPS, SSH, SRTP pass-through

NAT traversal

DoS and overload protection

Rate limiting

Dynamic black listing

Media Security Features

Media profiling

Roque RTP detection

Packet rate monitoring, and limiting

Bandwidth determination and enforcement

IMS, IPX and VoLTE

Interconnect Border Control Function (I-BCF)

Transition Gateway (TrGW) (RFC 4117), e.g., with Dialogic® I-Gate® 4000 PRO Media Gateway

 $Integrated\ Border\ Function\ (I-SBC)$

Interworking Function (IWF)

- SIP and SIP-I/SIP-T Interworking

Session Admission Control

License control

Inbound, outbound and aggregate call control
Session rate limit on per Peer and Interface level

Routing

Signaling Static Routing: Interface-Interface and Peer/Interface

SIP Invite/3xx SIP redirect server routing

Integration with other routing engines through SOAP and bulk routing

Policy-based routing
SIP Message-based routing

Local DNS for URI to IP Address and Port mapping Routing resolution through external DNS (SRV, A, NAPTR)

Load-balancing and priority-based routing RFC 4904 Trunk Group Routing support

Emergency services call routing and call prioritization

SIP URN routing

Dynamic SIP REFER processing

Media Optional Media Termination

Separation of signaling and media over VLANs

Media NAT traversal Media tromboning

BorderNet[™] Session Border Controllers supercharge connections between networks, services and subscribers with ease and scale

Datasheet

QoS

QoS metrics Packets lost, jitter inter-arrival, and latency

Policy enforcement DSCP and ToS marking

Traffic statistics Total packets and octets transferred

Media Support

Audio G.711, G.722, G.723.1, G.726, G.729a, G.729b, AMR-NB, AMR-WB, iLBC

Fax G.711 fax, T.38

Tones G.711 tones, SIP INFO, RFC 2833

Scalability

Base Configuration - per instance

Maximum Session Attempts Capacity 30 sessions per second (signaling and media)

Maximum Sessions 8,000 sessions

VLANs 12

IP Addresses 128 (signaling and media)

SIP Interfaces 64

Management

Integrated web-based management (https) dashboard and analytics

SNMP traps

Historical and real time statistics and reports

Business and engineering reports including report filtering and multi-format data export

Session Detail Records

Role based User Management

Integrated Wireshark packet and session tracing

Northbound API interface based on web technology (SOAP/XML)

Bulk provisioning interface

 $\mathsf{Dialogic}^{\texttt{@}}\,\mathsf{ControlSwitch}^{\texttt{\tiny{TM}}}\,\mathsf{System}\,\mathsf{integration}$

- Integrated configuration and provisioning
- Integrated alarms and reporting
- Unified Call Detail Record (CDR)
- End-to-end session tracing
- EMS platform manages both BorderNet Virtualized SBC and ControlSwitch System

Interfaces (Virtual)

Signaling and Media Two (2) 1 Gigabit Ethernet Interfaces

Management One (1) Gigabit Ethernet
High Availability One (1) Gigabit Ethernet

Hypervisor

VMWare vSphere 5.0 or higher

Minimum Hardware Specification for Virtual Machines

Base Configuration

Server CPU: 2.4 GHz x86 64-bit Processor, 300 GB storage

Per instance – up to 2 instances • Cores: 2

- 4GB RAM
- 80GB Storage
- Four (4) 1 Gigabit Ethernet Interfaces



www.dialogic.com

For a list of Dialogic locations and offices, please visit: https://www.dialogic.com/contact.aspx

Dialogic, BorderNet, I-Gate, and ControlSwitch are either registered trademarks or trademarks of Dialogic Corporation and its affiliates or subsidiaries ("Dialogic"). Dialogic's trademarks may be used publicly only with permission from Dialogic. Such permission may only be granted by Dialogic's legal department at 6700 de la Cote-de-Liesse Road, Suite 100, Borough of Saint-Laurent, Montreal, Quebec, Canada H4T 2B5. The names of actual companies and products mentioned herein are the trademarks of their respective owners.

Dialogic encourages all users of its products to procure all necessary intellectual property licenses required to implement their concepts or applications, which licenses may vary from country to country. None of the information provided in this Datasheet other than what is listed under the section entitled Technical Specifications forms part of the specifications of the product and any benefits specified are not guaranteed. No licenses or warranties of any kind are provided under this datasheet.

Dialogic may make changes to specifications, product descriptions, and plans at any time, without notice.

Any use case(s) shown and/or described herein represent one or more examples of the various ways, scenarios or environments in which Dialogic® products can be used. Such use case(s) are non-limiting and do not represent recommendations of Dialogic as to whether or how to use Dialogic products.

This document discusses one or more open source products, systems and/or releases. Dialogic is not responsible for your decision to use open source in connection with Dialogic products (including without limitation those referred to herein), nor is Dialogic responsible for any present or future effects such usage might have, including without limitation effects on your products, your business, or your intellectual property rights.